

LISTING OF CLAIMS

1. (currently amended) A method for uniquely authenticating each replication of a plurality of soft-copy documents, said plurality of soft-copy documents forming a group, comprising the steps of: [[;]]

dynamically selecting one soft-copy document out of said group to become a carrier for an authentication code aimed at protecting said group;

concatenating said plurality of soft-copy documents, said concatenating including the step of using a canonical form of said selected soft-copy document;

computing an authentication code from said concatenated plurality of soft-copy documents and a predetermined key;

generating a random number; and

creating said carrier by combining said random number and said authentication code and marking said selected soft-copy document.

2. (original) The method according to claim 1 wherein said step of concatenating uses all of said plurality of soft-copy documents with the exception of said selected soft-copy document.

3. (original) The method according to claim 1 wherein said step of concatenating is replaced by the step of picking up a single soft-copy document.

4. (original) The method according to claim 1 wherein the creating said carrier comprises the steps of:

splitting said selected soft-copy document into a first set of data and a second set of data on the basis of said authentication code;

utilizing said random number to mark said first set;

transforming said random number;

utilizing said transformed random number to mark said second set; and

reassembling said first set and said second set into said carrier.

5. (original) The method according to claim 1 wherein said selected soft-copy document is a plain text document and said first set and said second set comprise sets of words from said plain text document.
6. (original) The method according to claim 5 wherein said plain text document is marked through the insertion of extra blanks.
7. (original) The method according to claim 6 wherein the step of using said canonical form of said plain text document includes the step of:
- stripping all interword blank characters, in excess of one, off said plain text document; thereby, obtaining said canonical form.
8. (original) The method according to claim 4 wherein said selected soft-copy document is a plain text document and said first set and said second set comprise sets of words from said plain text document.

FR920000021-US1

-4-

9. (original) The method according to claim 8 wherein said plain text document is marked through the insertion of extra blanks.

10. (original) The method according to claim 9 wherein the step of using said canonical form of said plain text document includes the step of:

stripping all interword blank characters, in excess of one, off said plain text document; thereby, obtaining said canonical form.

11. (original) The method according to claim 4 wherein said authentication code, said random number, said transformed random number are binary vectors fitting respectively in said selected soft-copy document, said first set and said second set.

12.(original) The method according to claim 4 wherein said splitting step includes the steps of:

forming said first set with the words from said selected soft-copy document corresponding to the ones of said authentication code; and

forming said second set with the words from said selected soft-copy document corresponding to the zeros of said authentication code.

FR920000021-US1

-6-

13.(original) The method according to claim 1 wherein said computing step comprises the steps of:

computing said authentication code from said concatenated plurality of soft-copy documents, said key and a counter; testing said authentication code for a prespecified range of zero values to one values;

if said code does not fall within said prespecified range:

incrementing said counter; and

resuming at computing step; and

if said code does fall within said prespecified range:

validating said authentication code; and

exiting said computing step.

14.(original) The method according to claim 4 wherein said computing step comprises the steps of:

computing said authentication code from said concatenated plurality of soft-copy documents, said key and a counter;

testing said authentication code for a prespecified range of zero values to one values;

if said code does not fall within said prespecified range:

incrementing said counter; and

resuming at computing step; and

if said code does fall within said prespecified range:

validating said authentication code; and

exiting said computing step.

15.(original) The method according to claim 4 wherein said transforming step includes:

hashing said random number;

reusing said random number; and

inverting said random number.

16. (canceled)

17. (currently amended) A system for uniquely authenticating each replication of a group of soft-copy documents, comprising:

a selection component for dynamically selecting one soft-copy document out of said group to become a carrier for an authentication code aimed at protecting said group;

a concatenation component for concatenating said plurality of soft-copy documents, said concatenating including the step of using a canonical form of said selected soft-copy document;

a processor for computing an authentication code from said concatenated plurality of soft-copy documents and a predetermined key;

a generating component for generating a random number;
and

carrier marking means for creating said carrier by combining said random number and said authentication code and marking said selected soft-copy document.

FR920000021-US1

-9-

18. (original) The system of claim 17 wherein the carrier marking component comprises:

a splitter component for splitting said selected soft-copy document into a first set of data and a second set of data on the basis of said authentication code;

a transformation component for transforming said random number;

a marking component for utilizing said random number to mark said first set and for utilizing said transformed random number to mark said second set; and

an assembly component for reassembling said first set and said second set into said carrier.

19. (currently amended) A ~~computer like readable medium~~
program storage device readable by machine tangibly
embodying a program of instructions executable by the
machine for uniquely authenticating each replication of a
plurality of soft-copy documents, said plurality of
soft-copy documents forming a group, said method comprising
the steps of:

dynamically selecting one soft-copy document out of said
group to become a carrier for an authentication code
aimed at protecting said group;

concatenating said plurality of soft-copy documents, said
concatenating including the step of using a canonical
form of said selected soft-copy document;

computing an authentication code from said concatenated
plurality of soft-copy documents and a predetermined key;

generating a random number; and

creating said carrier by combining said random number and
said authentication code and marking said selected
soft-copy document.